

2015 Log

Date	Topic	Page	Note				
Jan.6th	Special Options	ND k-2	Batten Size for Type E/F (Add Batten width column)				
Jan. 6th	2014 Track Shutter-90 Bifold	ND j1-11	Hang Strip for Inside Mount Only				
			Louver Size Maximum Possible Louvers Height Range				
Jan.15th	Tilt Rod	ND g-1	2½" 24 54 3/4" - 57 1/4" 3½" 16 54 3/4" - 58" 4½" 12 54 3/4" - 60"				
Jan.15 th	Track Shutter-Bypass	ND J2-1~ND J2-11	Old Track Shutter-Bypass discontinue(delete page1~11)				
Jan.15 th	Stile Options	ND c-1	Delete Center Stile				
Jan.23 rd	Closed bypass with 3 tracks	ND j2-5	Header size changed to 7 7/8"				
Jan.26 th	Bifold&Bypass	ND j1-1,7,j2-1	Remove the wording "2014" and just use Bi-fold 180 TM ? For 90 degree, it will be Bi-fold 90. The bypass section also remove "2014"				
Jan.29 th	Bifold	ND j1-3	Change extension for header supply loose to pre-attached				

Tab	ole of Contents	<u>Page</u>
a.	Features & Benefits	ND a-1
b.	Colors & Louvers	ND b-1
c.	Stiles	ND c-1
d.	Panel Configurations	ND d-1
e.	Frame Styles	ND e-1
f.	General Product Specifications	ND f-1
g.	Tilt Rods	ND g-1
h.	Divider Rails	ND h-1
i.	Hardware	ND i-1
j.	Track Shutters	ND j-1
k.	Special Options	ND k-1
1.	Specialty Shapes	ND 1-1
m.	Pricing	ND m-1
n.	Appendix	ND n-1




Features and Benefits

- Brings a touch of timeless elegance to your home. The **textured finish of Normandy shutters** blends the tranquility of nature with distinctive luxury.
- Normandy is treated with our exclusive Prescription Wood Conditioning[™] technique according to the moisture content of the final installation location to reduce postinstallation shrinking and swelling.
- A wide range of frames with inserts that keep installation screws out of sight for a clean and decorative look to match any style and preference.
- Reinforced engineered stiles -- Multiple layers of wood bonded together to reinforce durability to the core of the stile, which results in a robust support system for the shutter panel.
- Multiple stile options available in various sizes to accommodate different window configurations. Astragal (solid color shutters only) or Rabbet stiles provide a natural light block between panels.
- Employs mortise and tenon joinery that resists shear and racking forces endured by shutters and ensures prolonged stability and durability.
- Quick and easy on-site installation with the **pre-installed magnets and hinges**, as well as **pre-mitered frames** and **slotted keyholes**.
- Labor-intensive hand finishing process involves multiple sequences of sanding and coating with fine layers of stain or paint for a brilliant, lustrous finish.
- Personalize shutters with **special options.** Choose from hidden or offset tilt rods, double-hung panels, café shutters, track systems, specialty shapes and many more.
- Special panel and frame designs are finely crafted to accommodate unique window configurations. Create unity or attract attention with Normandy's exclusive decorative elements.
- Available in classic paint and radiant stain that harmonize into the style of any home.
- A guarantee of Norman's exemplary quality with a lifetime limited warranty on materials and workmanship.

Colors & Louvers

Solid Colors	Lo	uvers
001 Pure White		
003 Silk White		
004 Bright White		
006 Pearl		
009 Creamy		
012 Crisp Linen		
030 Moondust		
046 Ice		
Stain Colors*		
108 Rustic Gray		
110 Limed White		04.00
205 Goldenrod		2½"
211 Cherry	Elliptical	3½"
221 Black Walnut		0,1
227 Red Oak		4½"
229 Rich Walnut		
230 Old Teak		
231 Spring Rose		
232 Red Mahogany		
233 Dark Mahogany		
237 Wenge		
242 Auburn		
249 Acorn		
250 Sumatra		
Opti	mal™*	




Optimal™ safeguards your window treatments from accumulating airborne germs and disease-causing bacteria so that you have on less thing to worry about.

** Custom sheen options available

Colors available till June 30, 2013				
Color Code	Color Name	Note		
011	Cameo	Discontinue on June 30, 2013		
013	Bisque	Discontinue on June 30, 2013		
103	Maple Sugar	Discontinue on June 30, 2013		
105	Hermitage Green	Discontinue on June 30, 2013		
206	Pecan	Discontinue on June 30, 2013		
214	Cocoa	Discontinue on June 30, 2013		
222	Light Pine	Discontinue on June 30, 2013		
224	Mellow Beech	Discontinue on June 30, 2013		
226	Chestnut	Discontinue on June 30, 2013		

Stiles Options



Stile between panel closure

Single panel

- I) Panel width < 9"
 - Rabbeted stile (Deco frame, L frame, Z frame and Hang strip beside panel



° 2" (default)

Butt stile only (Hang strip behind panel)

° 2" (default)




- II) Panel width > 9"
 - Butt stile only
 - $^{\circ}$ 1 $^{5}/_{8}$ " (Optional for panel width ≤ 12")
 - ° 2" (default)

2 panels or more


- Astragal stile
 - \circ 1 $^{5}/_{8}$ " (Optional for panel width \leq 12")
 - ° 2" (default)
- Rabbet stile
 - \circ 1 $\frac{5}{8}$ " (Optional for panel width \leq 12")
 - ° 2"

Panel Configurations


Single Panel




2 Panels



3 Panels




4 Panels




Panel Configurations (continued)

6 Panels






Panel Configurations – Astragal Stile



Frame Styles




Also available

Custom extensions* up to 2" for L frames

^{*}Surcharge applies. Please see Options and Surcharges page for details.


Frame Styles




Also available


- Custom extensions* up to 1" for Z frames
- \circ ½", 1" and 1½" standard extensions and custom extensions up to 2" for Deco frames ND e-2
- Custom extensions* up to 2" for hang strips (OM)

Frame Styles







Curved Designer Sill Cap (L) Curved Designer Sill Cap (D/HS) Curved Designer Sill Cap (Z)




ND e-4

Frame Styles






Frame Styles



Also available

- \circ Custom depth* up to 2" / width* up to 7½ for T Posts
- Custom angle bay posts*

Pre-drill L or Z frames:



^{*} Surcharge applies. Please see Options and Surcharges page for details



General Product Specifications

Description	<u>Minimum</u>	<u>Maximum</u>
Single Panel Width (Regular)	6"	42" for 3.5"&4.5" louvers, 36" for other louver type
Single Panel Width (Bifold)	6"	26"
Single Panel Width (for Bypass Panel With Center Stile)	6"	50"
Single Panel Height	10"	133"
Shutter Width (Without T Post)	N/A	4x single panel width (bifold) + frame
Shutter Width (With T Post)	N/A	Unlimited (frame* pieces exceeding 142" will be spliced)
Shutter Height	N/A	133" + frame

^{*} For frame and stile exceeding 108", there will be a visible finger joint line in the middle.

Shutters without bottom supports

Normandy shutters will be covered by our warranty for this application, subject to our standard specification limitations and the guidelines listed below:

All Normandy panel configurations:

- ♦ You must inform Norman Shutters of situations where shutters will not have bottom support when placing the initial order, or warranty will be considered void.
- Informing Norman Shutters when placing such orders ensures that the factory will add extra hinges to support the panel. This will reduce the probability of the panels sagging and increase shutter integrity.
- If you fail to notify Norman Shutters that the shutter will be used without a bottom support or used as doors, this will constitute a misapplication of the shutter. Consequently, you will be responsible for the cost of any RGA Reorder that is submitted.
- ♦ If you want a bifold shutter, a track must be ordered to support the panels.



Divider Rails

- A divider rail is an extra rail in the middle of the panel.
- Creates two sections in the panel so louvers can be operated independently.
- Strengthens the panel and enhances structural integrity.
- Divider rail is required for panel heights over 78".
- 84" panel height limit without divider rail is for Wood French Door installed with button catches & Wood Bypass and bi-fold track shutters.


Specifications

- Standard width: 3"
- Default location: center of the panel unless specified otherwise

Measurements:

- Window size:
 - Measure from the bottom of the window to the center of the divider rail.
- Max frame-to-frame:
 - Measure from the bottom of the frame to the center of the divider rail.
- Position:
 - Per customer's specification. However, the divider rail may be adjusted to a lower or higher position, within our allowable deviation, to ensure reinforcement and aesthetics of the shutter.

When placing the order, please clearly specify if the divider rail position needs to line up with that of other shutter divider rails in the same room. Please also refer to the table below for the allowable deviation details.




Divider rail allowable deviations

Louver Size	Allowable <u>+</u> Deviation
2½"	1"
3½"	1½"
4½"	2"




Tilt Rod



Standard Tilt Rod Default Location

In the middle of the panel on front side (default).




Offset Tilt Rod* Default Location

On the front side of the panel and at 1" from the louver ends on the hinged side.

Optional location: per your request.





Louver tilting system embedded within panel stile. It is not available for $1^7/8$ " louver. The tilting system is split when the number of louvers exceeds the limits as listed below:

Louver Size	Maximum Possible Louvers	Height Range
2½"	<mark>24</mark>	54 3/4" – 57 1/4"
3½"	<mark>16</mark>	54 3/4" – 58"
4½"	<mark>12</mark>	54 3/4" – 60"


- For even numbers of louvers, the number of louvers operated by the top and the bottom tilting system will be the same.
- For odd numbers of louvers, the number of louvers operated by the bottom tilting system will be one more than the number of louvers operated by the top tilting system.

^{*} Surcharge applies. Please see Options and Surcharges page for details.


Hardware

Hinges


Self-Mortise Hinge



Bi-fold Hinge



L Hinge



Hinges are available in:


Silk White, Bisque, Pearl, Bright Brass, Antique Brass, Black, Nickel plated and Stainless Steel*

Surcharge applies. Please see Options and Surcharges page for details.

Panel Lock: (not available for 1.625" Stile)


Available Material: All Color: Brush Nickel-Plated






Position: (Only available on Bottom for Track Shutters with Bottom Track; For Regular, available on Top/Bottom/both Top and Bottom)

Panel Config: RRR




Panel Config: LLL



The Panel Lock location for both track system shutters and regular shutters would be the same.


The general principle is that the Panel Lock position will avoid the still which will install the spring-loaded gu

The general principle is that the Panel Lock position will avoid the stile which will install the spring-loaded guide at bottom (same stile as the Wheel carrier).



Ring pull: for easy opening and closing

(Not available for 1.625" Stile)




Please note the ring pull finish will match with the hinge finish.

Please see the matching chart below:

Hinge	White	Bisque	Pearl	Black	Nickel	Brushed Nickel	Oil- Rubbed	Antique Brass	Bright Brass	Stainless Steel
Ring Pull	White	Bisque	Pearl	Black	Brushed Nickel	Brushed Nickel	Black	Antique Brass	Bright Brass	Brushed Nickel

Position: For different panel configuration, please refer to the location of Panel Lock to show on which stile the pull will be fixed.




Position:

- A. Above Bottom Rail (Default)
- B. Above 1st Divider Rail (Default when there are Divider Rails)
- C. Custom Location

If both Panel Lock & ring pull are specified, the distance between them is 2 3/4", and the ring pull location is 6 3/4" from the bottom of panel.

When there is no mid rail, ring pull will be just on the top of Panel Lock (2 3/4" above Panel Lock) as default location; if there are mid rails, bottom of ring pull lines up with top of the 1st mid rail as default location.



Position:

- A. 2 3/4" Above Panel Lock (Default when both Ring Pull and Panel Lock are specified)
- B. Above 1st Divider Rail (Default when there are Divider Rails)
- C. Custom Location

Measurements:

- · Window size:
 - Measure from the bottom of the window to the center of the ring pull.
- Max frame-to-frame:
- Measure from the bottom of the frame to the center of the ring pull.

Invisible Hinge

Available Material: ALL Except Woodbury		
·		
Frame Options	Hinge	Notes
2" Camber Deco Frame	Y	/
2" Classic Deco Frame	Y	/
3" Ridge Deco Frame	N	/
Vintage L Frame W / 1/4" Light Block	N	/
Vintage L	N	1
Vintage L Frame w/ 1/2" Buildout	N	/
Vintage L Frame w/ 1" Buildout	N	/
Beaded L w 1/4"light block	Υ	/
Beaded L	Υ	/
Beaded L Frame w/ 1/2" Buildout	Υ	/
Beaded L Frame w/ 1" Buildout	Υ	/
Bullnose L	N	1
Bullnose L Frame w/ 1/2" Buildout	N	/
Bullnose L Frame w/ 1" Buildout	N	/
Tilt out Z Frame	N	1
1.25" Beaded Z Frame	Υ	/
1.5" Bullnose Z Frame	Υ	1
2" Bel Air Z Frame	Υ	1
3" Crown Z Frame	N	/
7/8" Vintage Hang Strip (31mm) (27mm for 1" stile)	N	/
1" T-Post w/ 1/4" Light Block(for Deco)	Y	only available with hinge on
1" T-Post w/3/4" Light Block(for L/Z/HS)	Y	one side, for example, LTL is available, but RTL is not.
1 3/4" T-Post w/1/4" Light Block(for Deco)	Y	available with hinge on BOTH
1 3/4" T-Post w/3/4" Light Block(for L/Z/HS)	Y	side, for example, RTL.
	•	•

Corner Post w/1/4" Light Block(for Deco)	Y	/
Corner Post w/3/4" Light Block(for L/Z/HS)	Y	/
Bay Post w/1/4" Light Block(for Deco)	Y	/
Bay Post w/3/4" Light Block(for L/Z/HS)	Y	/
Invisible Hinge Qty		
Panel Height (H)	Hinge Qty	
H<=48"	2	
48" <h<=78"< td=""><td>3</td><td></td></h<=78"<>	3	
78" <h<=96"< td=""><td>4</td><td></td></h<=96"<>	4	

5

Available Stile:Butt and Astragal

96"<H<=120"

H>120"

Preinstallation:

Panels and frames will be packaged individually, and the hinge is preinstalled onto the frame/post, with the screws for the other half part on the panels in the hardware box.


If bifold/multi-fold panels are packaged together, the hinges are installed before shipping, or the hinges & screws are packed into the hardware box.

Side Magnet: Only available for Butt and Astragal stile




For Shutter with Astragal Stile, Side Magnets will be applied in following situation:

Double Hung shutter but without horizontal T post:
 Side magnets will be applied to the meeting stiles of the L and R panel. (Default)




2. Café Shutter

Side magnets will be applied to the meeting stiles of the L and R panel. (Default)



3. No frame or light block or L-shape striker plate on either top or bottom, or if larger than standard top or bottom gap is requested.

Side magnets will be applied to the meeting stiles of the L and R panel. (Optional)






Bi-fold 180TM

Guidelines and Specs:

Description		<u>Maximum</u>			
<u>Description</u>	<u>Minimum</u>	1 1/4"	1 7 8"	2½"; 3½"; 4½"	
Single-Panel Width (Bi-fold Track)	6"	N/A	26"	26"	
Single-Panel Width (LLL/RRR)	6"	N/A	20"	20"	
Single-Panel Height	10"	N/A	133"	133"	

Outside Mount

Max frame-to-frame width: window width + 3 1/2"
Max frame-to-frame height: window height + 3




• Track is pre-installed on the header; standard 1 track only.




Mounting Options: Outside Mount only

Side View




Top View

Without Casing:



With Existing Casing:




Note:


- ♦ Fascia return will protrude the panel about 1/2" for each side.
- ♦ The header will protrude the panel about 1/8" for each side.
- Header, light blocks, and bottom pivot bracket(s) must be installed on a flat surface.



- ♦ Header Extension: Optional
- ♦ Custom extension up to 2" for Header
- ♦ When extension is needed, the header will protrude the panel 5/16" for each side and the fascia return will protrude the panel 11/16" for each side.




♦ The extension will be pre-attached.




Panel Configuration: Only 2", 2 1/4" astragal and butt stile is available. Center and Rabbet stile is not available.









 RR




LLL (Wood only)




RRR (Wood only)



LLRR:



LLLRRR (Wood only)




Notes:

If there is no baseboard to the wall, 3" header can be used.

If there is baseboard to the wall, then it should be as below:

- 1. If base board thickness is less or equal to 5/8", 3 1/2" header can be used.
- 2. If base board thickness is over 5/8", it is suggest using the 3" header with build out. And the build out thickness=base board thickness-1/8".

Please see the drawing below:



Normandy Shutters

180° Bi-fold Track Shutters Framing Materials

Туре	Header Dimension	Top Fascia Dimension	L Shape Light Block Strip Dimension
Header & Top Fascia &	3"	4.7/01	1 1/2"
Light Block Strip	3 1/2"	1 7/8"	2 "

180⁰ Bi-fold Track Shutters Hardware Box

Parts
Wrench
Hinge Pin
Bottom Pivot Bracket
1 ½ " screws for bottom pivot bracket
2 ½ " screws for Frame



Bi-fold 90

Guidelines and Specs:


<u>Description</u>	<u>Minimum</u>	<u>Maximum</u>		
		1 1/4"	17⁄8"	2½"; 3½"; 4½"
Single-Panel Width (Bi-fold Track)	6"	N/A	26"	26"
Single-Panel Width (Multifold track up to 4 panels)	6"	N/A	20"	20"
Single-Panel Height	10"	N/A	133"	133"

Outside Mount

Max frame-to-frame width: window width + 3 1/2" Max frame-to-frame height: window height + 3"


Inside Mount & Semi-Inside Mount

Max frame-to-frame width: window width - 1/8"
Max frame-to-frame height: window height - 1/8"



Track is pre-installed on the header; standard 1 track only.


Mounting Options: Outside Mount




Without Casing:

Note:

- $\diamondsuit\,$ Fascia return will protrude the panel about 1/2" for each side.
- ♦ The header will protrude the panel about 1/8" for each side.
- ♦ Header, light blocks, and bottom pivot bracket(s) must be installed on a flat surface.



With Existing Casing:






Inside Mount


Side View

Inside Mount

Semi-Inside Mount




Top View








- ♦ Header Extension: Optional.
- ♦ Custom extension up to 2" for Header
- ♦ The extension will be supplied loose with installation screws.



Panel Configuration: Only 2", 2 1/4" astragal and butt stile is available. Center stile and Rabbet is not available.









90° Multi-Fold Track Shutters (Wood only)


Maximum single panel width for multi-fold is 20" Panel Configuration: LLLL, RRRR, or LLLLRRRR



90⁰ Floating Panels



Note: For 90° Floating Panels outside mount, T Stopper will be supplied and the fascia return will protrude panel 3/4" for each side.



90 Degree Bi Fold Track Shutters Framing Materials


Ту	pe	Header Dimension	Top Fascia Dimension	Light Block Strip Dimension	Hang Strip Dimension
	OM	3"		1 1/2"	
Header & Top Fascia&		3 1/2"	1 7/8"	2 "	
Light Block Strip	IM	3"	1 170	5/8"x3/4"	1.08"x0.875"
	Semi-IM	3"		5/8"x3/4"	


Note: It will be L shape light block strip for outside mount.


Ring Pull: The ring pull will be provided as default for both 90⁰ and 180⁰ Bifold Track Shutters. Customer need specify ring pull location on the order form. Ring pull location is measured from the floor to center of the ring pull in height direction.

Ring pull color will match the hinge color.

Please refer to below drawing of ring pull position for 180⁰ Bifold Track:








Track Dimension:


Top Track




Bottom Pivot Bracket for 90 degree bifold:



Extra Magnets will be supplied for Bifold hinges: (only for the most top and bottom hinges)



Side Magnet: applied to the meeting stiles of LR panels



Extra magnet and Side Magnet



90⁰ Bi Fold Track Shutters Hardware Box

Parts
Wrench
Hinge Pin
Bottom Pivot Bracket
38.1mm screws for bottom pivot bracket
63.5mm screws for Frame

Track Shutters—Bypass

Guidelines and Specs:

			<u>Maximum</u>					
<u>Description</u>	<u>Minimum</u>	1 ¼"	11/8"	21/2"	3½"; 4½"			
Single-Panel Width (Wood)	6"	20"	30"	36"	42"			
Single-Panel Height	10"	N/A	133"	133"	133"			

Outside Mount

Max frame-to-frame width: window width + 3" Max frame-to-frame height: window height + 4½"


Semi-Inside Mount

Max frame-to-frame width: window width - 1/8" Max frame-to-frame height: window height + 1 3/8"

Inside Mount

Max frame-to-frame width: window width - 1/8" Max frame-to-frame height: window height - 1/8"


2014 Track Shutters—Bypass




2014 Track Shutters—Bypass

Top View


Combi - joined Panels (optional)



For shutters with 4 or more panels, please select "side open" or "center open" Side Open



Center Open



Stile: Only 2", 2 1/4" astragal stiles are available,


1 5/8" astragal stile only used for combi-joined panels.

Center stile is not available.

Size Definition


For Semi-Inside/OM without side boards

For IM without side boards





Note: For Semi-Inside/OM without side boards bypass, T Stopper will be supplied.

Mounting Options (Closed Bypass) Side View




Bottom Guide






Outside Mount






Mounting Options (Closed Bypass with 3 Tracks):



Outside Mount

Inside Mount




Semi-Inside Mount




Mounting Options (Opened Bypass) Only available in 2 ½" and 3 ½" louver sizes


2 1/2" Louver




Outside Mount



3 1/2" Louver






Default Bottom Guide

Optional Interlocking Bottom Guide

Opened Bypass (Top View)



Pitch of track

Louwer	U shape bottor	m guide	Interlocking bottom guide		
Louvei	Regular Tilt Rod		Regular Tilt Rod	Invisible tilt	
2.5"	3 9/16"	2 3/4"	3 9/16"	3 9/16"	
3.5"	4 1/2"	3 5/8"	4 1/2"	4 1/2"	

Light block thickness for panel

Light block thickness for parier							
		U shape bot	ttom guide	Interlocking bottom guide			
Louv	er	Regular Tilt Rod	Invisible tilt	Regular Tilt Rod	Invisible tilt		
2.5"	h1	3/4"	3/4"	3/4"	3/4"		
2.5	h2	1 9/16"	3/4"	1 9/16"	1 9/16"		
3.5"	h1	1 3/16"	1 3/16"	1 3/16"	1 3/16"		

h2 1 15/16" 1 3/16" 1 15/16" 1 15/16"

Track Shutters Framing Materials



Framing		Size			Pc(s)													
L Shape Header	Header (Closed Bypass)	Header (Opened Bypass)	Supporting Strip															
(2 in 1)	3/4" x 51/2"* (Default for Outside Mount; Optional for Semi-Inside and Inside Mount)	³ ⁄ ₄ " x 6 ¹ ⁄ ₄ " [*] (2 ¹ ⁄ ₂ " Louver)	¾" x ¾"		1 pc													
Header with Supporting Strip	3/4" x 41/2"* (Default for Semi-Inside and Inside Mount; Optional for Outside Mount)	³4" x 7 ¹³ / ₁₆ "* (3½" Louver)																
	Custom [*] ≤ 8"	Custom * < 8"																
U Shape Side Frame	Side Frame (Closed Bypass)	Side Frame (Opened Bypass)	Supporting Strip	Side Fascia														
(3 in 1)	3/4" x 5 7/8"* (Default for Outside Mount; Optional for Semi-Inside and Inside Mount) 3/4" x 4 7/8"*	¾" x 6 ½" (2½" Louver)		3/8 ³ /8" X	2 pcs													
Side Frame with Supporting Strip	3/4" x 4 7/8" [*] (Default for Semi-Inside and Inside Mount; Optional for Outside Mount)	³¼" x 8½" [*] (3½" Louver)	%" X %4"	74 X 74	%" X %"	% X %4	3/ V 3/	% X %	% X %	% X %	94" X 94"	% X %4	%" X %"	%4" X %4"	%" X %4"	³ / ₄ " x ³ / ₄ "	11/4 "	
& Side Fascia	Custom [*] ≤ 8"	Custom * < 8"																
Top Fascia (Plain/Deco)	4" (Semi-inside and Outside Mount)																	
(1 1411 11 2 3 3 3)	½" x 2 ½" (Inside Mount)																	
Top Fascia Return	4" (Semi-inside and Outside Mount)																	
Netuiii	N/A (Inside Mount)																	




Hardware Box				
Part				
Wrench				
Nylon Guide				
3/4 " screws for Nylon Guide				
Support L Bracket (based on the length of header)				
2 ½ " screws for support L bracket				
3/4 " screws for support L bracket				

Special Options

Café Shutters*


- The top of the panel requires a special finish. Please indicate "café shutter" when placing orders.
- The shutter does not come with recessed magnet on top.






Double-Hung Shutters*

- For total number of panels, please include panels in both rows.
- For panel configuration, please provide panel fold for one row.
- The default location for the division point is the center unless specified otherwise.
- Horizontal T Post* can be added for increased structural integrity.





Fixed Louvers



Surcharge applies. Please see Options and Surcharges page for details.




Special Options

French Door Cut-out Collection

- Flush and offset cutout options are available in both curved and square French door cutout.
 Offset cutout is good option for French Door with molding around the glass.
- All French door cutouts are only available in L frame except Type E and F. The batten is placed behind the Type E/F panel to block light.

Louver size	Batten Width	Batten thickness
1 7/8" & 2 1/2"	<mark>3/4"</mark>	<mark>1"</mark>
<mark>3 1/2"</mark>	3/4"	<mark>1 3/8"</mark>
<mark>4 1/2"</mark>	<mark>3/4"</mark>	<mark>1 7/8"</mark>

For measurement details please refer to Form section.



^{*} Surcharge applies. Please see Options and Surcharges page for details.




Specialties

Specialty Shutters

Specialty shutters are made of hardwood, finished to match the beauty of all Norman shutters. Templates are required if it is an imperfect specialty. Delivery time is 8 weeks from the order confirmation date for all specialty shutters. Please refer to Specialties and Template Requirement sections for details.

All frames for specialty shutters will be made as solid frames (not with an insert). However, if there is a regular shutter below a specialty shutter and the frames for both shutters are separated by a divider strip, then the top frame will be made as a solid frame but the bottom frames will be made as regular frames with inserts. If the top frames and the side frames are not separated by a divider strip, both side frames and the bottom frames will be made as solid frames.



^{*}Surcharge applies. Please see Options and Surcharges page for details.

Pricing

1) By Max Frame-to-Frame N	leasurement:						
Regular Shutter							
Inside and Outside Mount		Width	Х	Height	/ 144	Х	\$/sq ft
Track Shutter**							
Inside		Width	х	Height	/ 144	Х	\$/sq ft
Semi-Inside and Outside Mour	nt	Width	Х	(Height-1½")	/ 144	х	\$/sq ft
2) By Net Panel Measuremer	nt:	Width	Х	Height	/ 144	х	\$/sq ft
3) By Window Size:							
	4-sided	(Width+4")	х	(Height+4")	/ 144	х	\$/sq ft
	3-sided with Designer Sill Cap	(Width+4")	х	(Height+8")	/ 144	х	\$/sq ft
2" Camber Deco Frame	3-sided with Sill Plate	(Width+4")	х	(Height+4")	/ 144	х	\$/sq ft
	3-sided	(Width+4")	х	(Height+2")	/ 144	Х	\$/sq ft
	2-sided with Designer Sill Cap	(Width+4")	х	(Height+6")	/ 144	х	\$/sq ft
	2 sided with Sill Plate	(Width+4")	х	(Height+2")	/ 144	х	\$/sq ft
	2-sided	(Width+4")	х	(Height)	/ 144	х	\$/sq ft
	4-sided	(Width+4 1/2")	х	(Height+4½")	/ 144	Х	\$/sq ft
	3-sided with Designer Sill Cap	(Width+4 1/2")	х	(Height+81/4")	/ 144	х	\$/sq ft
	3-sided with Sill Plate	(Width+4 1/2")	х	(Height+4½")	/ 144	х	\$/sq ft
3" Crown Z Frame	3-sided	(Width+4 1/2")	х	(Height+21/4")	/ 144	х	\$/sq ft
	2-sided with Designer Sill Cap	(Width+4 1/2")	х	(Height+6")	/ 144	х	\$/sq ft
	2-sided with Sill Plate	(Width+4 1/2")	х	(Height+21/4")	/ 144	х	\$/sq ft
	2-sided	(Width+4 1/2")	х	(Height)	/ 144	х	\$/sq ft

Pricing

I	4 -:	(\A/; -\t\ O 1/"\		/	/ 4 4 4	Τ.,	Φ/= = #
	4-sided	(Width+2 ½")	_	(Height+2½")	/ 144	+-	\$/sq ft
	3-sided with Designer Sill Cap	(Width+2 1/2")		(Height+7¼")	/ 144	_	\$/sq ft
	3-sided with Sill Plate	(Width+2 ½")		(Height+2½")	/ 144		\$/sq ft
2" Bel Air Z Frame	3-sided	(Width+2 ½")	Х	(Height+1¼")	/ 144	Х	\$/sq ft
	2-sided with Designer Sill Cap	(Width+2 1/2")	Х	(Height+6")	/ 144	х	\$/sq ft
	2-sided with Sill Plate	(Width+2 1/2")	Х	(Height+1¼")	/ 144	х	\$/sq ft
	2-sided	(Width+2 1/2")	х	(Height)	/ 144	х	\$/sq ft
	4-sided	(Width+2")	х	(Height+2")	/ 144	х	\$/sq ft
	3-sided with Designer Sill Cap	(Width+2")	х	(Height+7")	/ 144	х	\$/sq ft
	3-sided with Sill Plate	(Width+2")	х	(Height+2")	/ 144	х	\$/sq ft
1 ½ " Bullnose Z Frame	3-sided	(Width+2")	х	(Height+1")	/ 144	х	\$/sq ft
	2-sided with Designer Sill Cap	(Width+2")	Х	(Height+6")	/ 144	х	\$/sq ft
	2-sided with Sill Plate	(Width+2")	х	(Height+1")	/ 144	х	\$/sq ft
	2-sided	(Width+2")	х	(Height)	/ 144	х	\$/sq ft
	Inside	Width	х	Height	/ 144	х	\$/sq ft
	Outside 4-sided	(Width+3")	х	(Height+3")	/ 144	х	\$/sq ft
Vintage Hang Strip	Outside 3-sided with Designer Sill Cap	(Width+3")	х	(Height+7½")	/ 144	х	\$/sq ft
Village Hang Strip	Outside 3-sided	(Width+3")	х	(Height+1½")	/ 144	х	\$/sq ft
	Outside 2-sided with Designer Sill Cap	(Width+3")	х	(Height+6")	/ 144	х	\$/sq ft
	Outside 2-sided	(Width+3")	х	(Height)	/ 144	х	\$/sq ft
	Inside (max frame to frame measurement only)	Width	х	Height	/ 144	х	\$/sq ft
Beaded L Frame/	Outside 4-sided	(Width+3")	х	(Height+3")	/ 144	х	\$/sq ft
Colonial L Frame/	Outside 3-sided with Designer Sill Cap	(Width+3")	х	(Height+7½")	/ 144	х	\$/sq ft
Bullnose L Frame/	Outside 3-sided	(Width+3")	х	(Height+1½")	/ 144	х	\$/sq ft
Vintage L Frame	Outside 2-sided with Designer Sill Cap	(Width+3")	х	(Height+6")	/ 144	х	\$/sq ft
	Outside 2-sided	(Width+3")	х	(Height)	/ 144	х	\$/sq ft
Track Shutter**							
Inside and Semi-Inside Mount		Width	Х	Height	/144	Х	\$/sq ft
Outside Mount		(Width+3")	х	(Height+3")	/144	х	\$/sq ft

Options & Surcharges

Option	Surcharge	Remark
Beaded L Frame with ¼" Thick Light Block	No surcharge	
L Frame with ½" & 1" Buildout	5%	
Notch Out L Frame	12%	
Deco Frame with ½", 1" & 1½" Extension	5%	
Custom Extension	12%	Up to 2" for L Frames, Deco Frames and Hang Strip (OM)
Custom Extension	12%	Up to 1" for Z Frames (not available for Tilt Out Z frame)
T Post	No surcharge	
T Post Extension	5%	Up tp 2"
Custom width T Post	6%	Up tp 7½"
90 degree Corner Post & 135 degree Bay Post	No surcharge	
Double Hung / Horizontal 1¾" T Post	10%	
Custom Angle/Depth Bay Post	6%	Up to 2" for custom depth
Extra Light Block	Charge per linear ft	Please contact your Customer Account Specialist for details
Scribe Trim	Charge per linear ft	Please contact your Customer Account Specialist for details
Center Tilt Rod	No surcharge	
Offset Tilt Rod	5%	
InvisibleTilt™	10%	Panels over 48" will have a split InvisibleTilt tilt rod. Not available in 1" louvers.
Optimal™ Antimicrobial Treatment	10%	
Café Shutters	30%	Surcharge applies when the frame exceeds 5" beyond the top of the panel.
Fixed Louver Panel	No surcharge	Please indicate fixed position: up/down and open/close
French Door Cutout	See specialty surcharge	Please contact your Customer Account Specialist for details
Track (Bi Fold / Bypass)	40%	
Specialties	See specialty surcharge	Please contact your Customer Account Specialist for details
Stainless Steel Hinges	5%	
PerfectTilt (regular)	Per motor, per remote control	Please contact your Customer Account Specialist for details
PerfectTilt (solar)	Per motor, per remote control	Please contact your Customer Account Specialist for details



Appendix

Color Coordination Chart

Code / Normandy Solid	Hinge Color
001 Pure White	Silk White
003 Silk White	Silk White
004 Bright White	Silk White
006 Pearl	Pearl
009 Creamy	Bisque
011 Cameo	Bisque
012 Crisp Linen	Bisque
013 Bisque	Bisque
030 Moondust	Bisque




Code / Normandy Stain	Hinge Color
103 Maple Sugar	Antique Brass
105 Hermitage Green	Antique Brass
108 Rustic Gray	Antique Brass
110 Limed White	Antique Brass
205 Goldenrod	Antique Brass
206 Pecan	Antique Brass
211 Cherry	Antique Brass
214 Cocoa	Antique Brass
221 Black Walnut	Antique Brass
222 Light Pine	Antique Brass
224 Mellow Beech	Antique Brass
226 Chestnut	Antique Brass
227 Red Oak	Antique Brass
229 Rich Walnut	Antique Brass
230 Old Teak	Antique Brass
231 Spring Rose	Antique Brass
232 Red Mahogany	Antique Brass
233 Dark Mahogany	Antique Brass
237 Wenge	Antique Brass
242 Auburn	Antique Brass
249 Acorn	Antique Brass
250 Sumatra	Antique Brass



Louver Depth Clearance

Standard Tilt Rod

Offset Tilt Rod









Louver Depth Clearance For Specific Frames

Louver Depth Clearance for

• Offset tilt rod, add 1" from the edge of the louvers







Louver Depth Clearance For Specific Frames

