

2015 Log

Date	Topic	Page	Note				
Jan. 6th	Special Option	NT k-4	Batten Size for Type E/F (Add Batten width column)				
Jan. 6th	2014 Track Shutter-90 Bifold	NT j1-11	Hang Strip for Inside Mount Only				
			Louver Size	Height Range			
Jan.15th	Tilt Rod	NT g-1	2½"	<mark>24</mark>	54 3/4" – 57 1/4"		
			3½" 4½"	16 12	54 3/4" – 58" 54 3/4" – 60"		
Jan.15 th	Track Shutter-Bypass	NTj2-1~NTj2-12	Old Track Shu	tter-Bypass discontinue(delete	page1~12)		
Jan.15 th	Stile Options	NT c-1	Delete Center	Stile			
Jan.23 rd	Closed bypass with 3 tracks	NT j2-5	Header size cl	hanged to 7 7/8"			
Jan.26 th	Bifold&Bypass	NT j1-1,6,j2-1	Remove the wording "2014" and just use Bi-fold 180 TM ? For 90 degree, it will be Bi-fold 90. The bypass section also remove "2014"				
Jan.29 th	Bifold	NT j1-3	Change the extension for header supply loose to pre-attached				



<u>Tat</u>	ole of Contents	<u>Page</u>
a.	Features & Benefits	NT a-1
b.	Colors & Louvers	NT b-1
c.	Stiles	NT c-1
d.	Panel Configurations	NT d-1
e.	Frame Styles	NT e-1
f.	General Product Specifications	NT f-1
g.	Tilt Rods	NT g-1
h.	Divider Rails	NT h-1
i.	Hardware	NT i-1
j.	Track Shutters	NT j-1
k.	Special Options	NT k-1
1.	Specialty Shapes	NT 1-1
m.	Pricing	NT m-1
n.	Appendix	NT n-1



Features and Benefits


- Made of hand-selected NormanTeak[™] that is treated with Prescription Wood
 Conditioning[™] technique according to the moisture content of the final installation location to reduce post-installation shrinking and swelling.
- Louvers are made of **quarter-sawn wood** to ensure generations of durability. This tight, straight and parallel grain also enriches wood character in stain finish.
- The appearance of **furniture quality finish** and the **exceptional craftsmanship** gives Norman Teak shutters an instant feeling of art.
- A wide range of frame designs, that keep installation screws out of sight for a clean and decorative look.
- Reinforced engineered stile-- Multiple layers of wood bonded together to reinforce durability to the core of the stile, which results in a robust support system for the shutter panel.
- Employs **mortise and tenon joinery** that resists shear and racking forces endured by shutters to ensure prolonged quality and durability.
- Multiple stile options available in various sizes to accommodate different window designs. Use Astragal or Rabbet stile as a natural light block between panels.
- Quick and easy on-site installation with the **pre-installed magnets and hinges**, as well as **pre-mitered frames** and **slotted keyholes**.
- A labor-intensive **hand finishing** process that involves **multiple sanding and coatings** with fine layers of stain or paint to achieve a translucent and polished appearance.
- **Special panel and frame design** that is custom cut to accommodate unique windows. Create unity or attract attention with Sussex's exclusive decorative elements.
- Personalize shutters with special options. Choose from fixed louvers, center or offset tilt
 rod, double hung panels, café shutters, track systems, French door cutout, specialty shapes
 and many more.
- Available in a multitude of solid and stain colors that can match the style of any home.
- A guarantee of Norman's exemplary quality with a **lifetime limited warranty on materials and workmanship**.



Colors & Louvers

	Solid		Stain**		
001 Pure White	019 String	108 Rustic Gray	230 Old Teak		
003 Silk White	030 Moondust	110 Limed White	231 Spring Rose		
004 Bright White	032 Sea Mist	114 Taupe	232 Red Mahogany		
006 Pearl	046 Ice	200 Natural	233 Dark Mahogany		
007 Ivory Lace	048 Chai	202 Golden Oak	237 Wenge		
008 Marshmallow	049 Stone Grey	204 Oak Mantel	242 Auburn		
009 Creamy	051 Brown Grey	205 Goldenrod	247 Bark		
011 Cameo	053 Clay	206 Pecan	248 Pretzel		
012 Crisp Linen	063 Decorators White	211 Cherry	249 Acorn		
013 Bisque	013 Bisque 836 Classic Black		250 Sumatra		
016 Butter		214 Cocoa	251 Raisin		
L	ouver	215 Cordovan	252 Toffee		
	1 ¼ "	219 Mahogany			
	1 7/8"**	220 New Ebony			
Elliptical	2 ½" *	221 Black Walnut			
	3 ½" *	227 Red Oak			
4 1/2" *		229 Rich Walnut			
	Ont	imal™*			


Optimal™ safeguards your window treatments from accumulating airborne germs and disease-causing bacteria so that you have on less thing to worry about.



Surcharge applies. Please see Options and Surcharges page for details.



Stiles Options



Sussex® NormanTeak™ Shutters


Stile between panel closure

Single panel

- I) Panel width < 9"
 - Rabbeted stile (Deco frame, L frame, Z frame and Hang strip beside panel
 - ° 1 ⁵/₈"
 - ° 2" (default)
 - Butt stile only (Hang strip behind panel)
 - ° 1 ⁵/₈"
 - ° 2" (default)



- II) Panel width ≥ 9"
 - Butt stile only
 - $^{\circ}$ 1 $^{5}/_{8}$ " (Optional for panel width ≤ 12"
 - ° 2" (default)




2 panels or more

- Astragal stile
 - \circ 1 $^{5}/_{8}$ " (Optional for panel width \leq 12")
 - ° 2" (default)
- Rabbet stile
 - \circ 1 $^{5}/_{8}$ " (Optional for panel width \leq 12")
 - ° 2"




Panel Configurations






Two Panels




Three Panels






Panel Configurations (continued)

Four Panels




Six Panels






Panel Configurations —Astragal stile







Also available

38.1mm [1.500"] Bullnose L

o Custom extensions* up to 2" for L frames

38.1mm [1.500"]

Bullnose L Frame W/

1/2" Buildout


38.1mm [1.500"]

Buildout

Bullnose L Frame W/1"

^{*}Surcharge applies. Please see Options and Surcharges page for details.







Also available


- Custom extensions* up to 1" for Z frames
- o ½", 1" and 1½" standard extensions and custom extensions up to 2" for Deco frames
- Custom extensions up to 2 for hang strips (OM)

















Curved Designer Sill Cap (L) Curved Designer Sill Cap (D/HS) Curved

Curved Designer Sill Cap (Z)






Corner Post W/ 3/4" Light Block (L/Z/HS)




Corner Post W/ 1/4" Light Block (Deco)










Also available

- Custom width up to 7½ for T Posts
- Custom angle bay posts*

Pre-drill L or Z Frames:



^{*}Surcharge applies. Please see Options and Surcharges page for details



General Product Specifications

		<u>Maximum</u>				
<u>Description</u>	<u>Minimum</u>	1¼"	17/8"	2½" / 3½" / 4½"		
Single Panel Width (Regular)	6"	20"	30"	36" for 2½", 42" for 3½" & 4½"		
Single Panel Width (Bi-fold)	6"	20"	26"	26"		
Multi-fold Panels						
(hinged shutters, up to 4 panels)	6"	20"	N/A	N/A		
Multi-fold Panels						
(track shutters, up to 4 panels)	6"	N/A	20"	20"		
Single Panel Width (for Bypass Panel With Center Stile)	6"	N/A	50"	50"		
Single Panel Height	10"	133"	133"	133"		
Shutter Width (Without T Post) N/A		4x single panel width (bifold) + frame				
		Unlimited				
Shutter Width (With T Post)	ost) N/A (frame pieces exceeding 142"		exceeding 142" will be spliced)			
Shutter Height	N/A	133" + frame				

Shutters without bottom supports


Norman Teak shutters will be covered by our warranty for this application, subject to our standard specification limitations and the guidelines listed below:

All Norman Teak panel configurations:

- You must inform Norman Shutters of situations where shutters will not have bottom support when placing the initial order, or warranty will be considered void.
- Informing Norman Shutters when placing such orders ensures that the factory will add extra
 hinges to support the panel. This will reduce the probability of the panels sagging and increase
 shutter integrity.
- If you fail to notify Norman Shutters that the shutter will be used without a bottom support or used as doors, this will constitute a misapplication of the shutter. Consequently, you will be responsible for the cost of any RGA Reorder that is submitted.
- If you want a bifold shutter, a track must be ordered to support the panels.



Tilt Rods



Standard Tilt Rod Default Location

In the middle of the panel on front side (default).




Offset Tilt Rod Default Location

On the front side of the panel and at 1" from the louver ends on the hinged side.

Optional location: per your request.

InvisibleTilt™ *

Louver tilting system embedded within panel stile. It is not available for $1\frac{1}{8}$ " or $1\frac{1}{8}$ " louver. The tilting system is split when the number of louvers exceeds the limits as listed below:



Louver Size	Maximum Possible Louvers	Height Range
2½"	<mark>24</mark>	54 3/4" – 57 1/4"
3½"	<mark>16</mark>	54 3/4" – 58"
4½"	<mark>12</mark>	54 3/4" - 60"

- For even numbers of louvers, the number of louvers operated by the top and the bottom tilting system will be the same.
- For odd numbers of louvers, the number of louvers operated by the bottom tilting system will be one more than the number of louvers operated by the top tilting system.

^{*} Surcharge applies. Please see Options and Surcharges page for details.



Divider Rails

- A divider rail is an extra rail in the middle of the panel.
- Creates two sections in the panel so louvers can be operated independently.
- Strengthens the panel and enhances panel structural integrity.
- For 11/4" Colonial louver, divider rail is required for panel heights over 50".
- For other louver sizes, divider rail is required for panel heights over 78".


Specifications

- Standard width: 3"
- Default location: center of the panel unless specified otherwise

Measurements:

- Window size:
 - Measure from the bottom of the window to the center of the divider rail.
- Max frame-to-frame:
 - Measure from the bottom of the frame to the center of the divider rail.
- Position:
 - Per customer's specification. However, the divider rail may be adjusted to a lower or higher position, within our allowable deviation to ensure reinforcement and aesthetics of the shutter.

When placing the order, please clearly specify if the divider rail position needs to line up with that of other shutter divider rails in the same room. Please also refer to the table below for the allowable deviation details.



Divider rail allowable deviations


Louver Size	Allowable <u>+</u> Deviation
1¼"	1/2"
1"	3/4"
2½"	1"
3½"	1½"
4½"	2"




Hardware

Hinges


Self-Mortise Hinge



Bi-fold Hinge



L Hinge



Hinges are available in:

Silk White, Bisque, Pearl, Bright Brass, Antique Brass, Black, Nickel plated and Stainless Steel $\dot{}$


Surcharge applies. Please see Options and Surcharges page for details.



Panel Lock: (not available for 1.625" Stile)


Available Material: All Color: Brush Nickel-Plated






Panel Config: RRR

Position: (Only available on Bottom for Track Shutters with Bottom Track; For Regular, available on Top/Bottom/both Top and Bottom)




Panel Config: LLL





The Panel Lock location for both track system shutters and regular shutters would be the same.


The general principle is that the Panel Lock position will avoid the stile which will install the spring-loaded guide at bottom (same stile as the Wheel carrier).





Ring pull: for easy opening and closing

(Not available for 1.625" Stile)




Please note the ring pull finish will match with the hinge finish.

Please see the matching chart below:

Hinge	White	Bisque	Pearl	Black	Nickel	Brushed Nickel	Oil- Rubbed	Antique Brass	Bright Brass	Stainless Steel
Ring Pull	White	Bisque	Pearl	Black	Brushed Nickel	Brushed Nickel	Black	Antique Brass	Bright Brass	Brushed Nickel

Position: For different panel configuration, please refer to the location of Panel Lock to show on which stile the pull will be fixed.




Position:

- A. Above Bottom Rail (Default)
- B. Above 1st Divider Rail (Default when there are Divider Rails)
 C. Custom Location

NormanTeak[™] Shutters If both Panel Lock & ring pull are specified, the distance between them is 2 3/4", and the ring pull location is 6 3/4" from the bottom of panel.

When there is no mid rail, ring pull will be just on the top of Panel Lock (2 3/4" above Panel Lock) as default location; if there are mid rails, bottom of ring pull lines up with top of the 1st mid rail as default location.



Position:

- A. 2 3/4" Above Panel Lock (Default when both Ring Pull and Panel Lock are specified)
- B. Above 1st Divider Rail (Default when there are Divider Rails)
- C. Custom Location

Measurements:

- Window size:
 - Measure from the bottom of the window to the center of the ring pull.
- Max frame-to-frame:
- Measure from the bottom of the frame to the center of the ring pull.



Invisible Hinge

myisibic minge		_
Available Material: ALL Except Woodbury		
Frame Options	Hinge	Notes
2" Camber Deco Frame	Υ	/
2" Classic Deco Frame	Υ	1
3" Ridge Deco Frame	N	/
Vintage L Frame W / 1/4" Light Block	N	/
Vintage L	Ν	1
Vintage L Frame w/ 1/2" Buildout	N	/
Vintage L Frame w/ 1" Buildout	N	/
Beaded L w 1/4"light block	Y	/
Beaded L	Υ	1
Beaded L Frame w/ 1/2" Buildout	Υ	/
Beaded L Frame w/ 1" Buildout	Υ	/
Bullnose L	N	1
Bullnose L Frame w/ 1/2" Buildout	N	/
Bullnose L Frame w/ 1" Buildout	N	/
Tilt out Z Frame	N	1
1.25" Beaded Z Frame	Υ	/
1.5" Bullnose Z Frame	Υ	1
2" Bel Air Z Frame	Υ	1
3" Crown Z Frame	N	/
7/8" Vintage Hang Strip (31mm) (27mm for 1" stile)	N	/
1" T-Post w/ 1/4" Light Block(for Deco)	Υ	only available with hinge on one side, for example, LTL is
1" T-Post w/3/4" Light Block(for L/Z/HS)	Υ	available, but RTL is not.
1 3/4" T-Post w/1/4" Light Block(for Deco)	Υ	available with hinge on BOTH
1 3/4" T-Post w/3/4" Light Block(for L/Z/HS)	Υ	side, for example, RTL.



Corner Post w/1/4" Light Block(for Deco)	Υ	/
Corner Post w/3/4" Light Block(for L/Z/HS)	Y	/
Bay Post w/1/4" Light Block(for Deco)	Υ	/
Bay Post w/3/4" Light Block(for L/Z/HS)	Y	/
Invisible Hinge Qty		
Panel Height (H)	Hinge Qty	
H<=48"	2	
48" <h<=78"< td=""><td>3</td><td></td></h<=78"<>	3	
78" <h<=96"< td=""><td>4</td><td></td></h<=96"<>	4	
96" <h<=120"< td=""><td>5</td><td></td></h<=120"<>	5	
H>120"	6	

Available Stile: Butt and Astragal

Preinstallation:

Panels and frames will be packaged individually, and the hinge is preinstalled onto the frame/post, with the screws for the other half part on the panels in the hardware box.

If bifold/multi-fold panels are packaged together, the hinges are installed before shipping, or the hinges & screws are packed into the hardware box.




Side Magnet: Only available for Butt and Astragal stile




For Shutter with Astragal Stile, Side Magnets will be applied in following situation:

Double Hung shutter but without horizontal T post:
 Side magnets will be applied to the meeting stiles of the L and R panel. (Default)




2. Café Shutter

Side magnets will be applied to the meeting stiles of the L and R panel. (Default)



3. No frame or light block or L-shape striker plate on either top or bottom, or if larger than standard top or bottom gap is requested.

Side magnets will be applied to the meeting stiles of the L and R panel. (Optional)






Bi-fold 180TM

Guidelines and Specs:

Description	tion <u>Minimum</u>	<u>Maximum</u>			
<u>Description</u>		1 1/4"	1 7 "	2½"; 3½"; 4½"	
Single-Panel Width (Bi-fold Track)	6"	N/A	26"	26"	
Single-Panel Width (LLL/RRR)	6"	N/A	20"	20"	
Single-Panel Height	10"	N/A	133"	133"	

Outside Mount


Max frame-to-frame width: window width + 3 1/2" Max frame-to-frame height: window height + 3



• Track is pre-installed on the header; standard 1 track only.




Mounting Options: Outside Mount only Side View




Top View





With Existing Casing:





Note:

- ♦ Fascia return will protrude the panel about 1/2" for each side.
- ♦ The header will protrude the panel about 1/8" for each side.
- ♦ Header, light blocks, and bottom pivot bracket(s) must be installed on a flat surface.




- ♦ Header Extension: Optional
- ♦ Custom extension up to 2" for Header
- ♦ When extension is needed, the header will protrude the panel 5/16" for each side and the fascia return will protrude the panel 11/16" for each side.






Panel Configuration: Only 2", 2 1/4" astragal and butt stile is available. Center and Rabbet stile is not available.


LL



RR








If there is no baseboard to the wall, 3" header can be used.

If there is baseboard to the wall, then it should be as below:

- 1. If base board thickness is less or equal to 5/8", 3 1/2" header can be used.
- 2. If base board thickness is over 5/8", it is suggest using the 3" header with build out. And the build out thickness=base board thickness-1/8".

Sussex® NormanTeak™ Shutters

Please see the drawing below:



180^o Bi-fold Track Shutters Framing Materials

Туре	Header Dimension	Top Fascia Dimension	L Shape Light Block Strip Dimension
Header & Top Fascia &	3"	1 7/8"	1 1/2"
Light Block Strip			2 "

180⁰ Bi-fold Track Shutters Hardware Box

Parts
Wrench
Hinge Pin
Bottom Pivot Bracket
1 ½ " screws for bottom pivot bracket
2 ½ " screws for Frame



Bi-fold 90


Guidelines and Specs:

<u>Description</u>	<u>Minimum</u>	<u>Maximum</u>		
		1 1/4"	17/8"	2½"; 3½"; 4½"
Single-Panel Width (Bi-fold Track)	6"	N/A	26"	26"
Single-Panel Width (Multifold track up to 4 panels)	6"	N/A	20"	20"
Single-Panel Height	10"	N/A	133"	133"

Outside Mount

Max frame-to-frame width: window width + 3 1/2" Max frame-to-frame height: window height + 3"


Inside Mount & Semi-Inside Mount
Max frame-to-frame width: window width - 1/8"
Max frame-to-frame height: window height - 1/8"



Track is pre-installed on the header; standard 1 track only.




Mounting Options: Outside Mount




Without Casing:

Note:

- ♦ The header will protrude the panel about 1/8" for each side.
- Header, light blocks, and bottom pivot bracket(s) must be installed on a flat surface.



With Existing Casing:





Window height

1<u>17</u>"


17"

<u>7</u>"

Semi-Inside/Inside Mount


Side View

Semi-Inside Mount




Semi-Inside Mount Top View






Inside Mount Top View




- ♦ Header Extension: Optional.
- ♦ Custom extension up to 2" for Header
- ♦ The extension will be supplied loose with installation screws.




Panel Configuration: Only 2", 2 1/4" astragal and butt stile is available. Center and Rabbet stile is not available.

Sussex®
NormanTeak™ Shutters


LL



RR




LLRR:




90° Multi-Fold Track Shutters (Wood only)

Maximum single panel width for multi-fold is 20" Panel Configuration: LLLL, RRRR, or LLLLRRRR




90° Floating Panels

Sussex®
NormanTeak™ Shutters




Note: For 90⁰ Floating Panels outside mount/semi-inside mount with return, T Stopper will be supplied and the fascia return will protrude panel about 19mm for each side.

Outside Mount Top View










Optional (Hang Strip for Inside Mount Only)

Sussex®
NormanTeak™ Shutters



Note: When Butt Stile is required, the stile next to the hang strip will be astragal stile.





90 Degree Bi Fold Track Shutters Framing Materials


Туре		Header Dimension	Top Fascia Dimension	Light Block Strip Dimension	Hang Strip Dimension
Header & Top Fascia&	ОМ	3" 3 1/2"		1 1/2"	
Light Block	IM	3"	1 7/8"	5/8"x3/4"	1.08"x0.875"
Strip	Semi-IM	3"		5/8"x3/4"	

Note: It will be L shape light block strip for outside mount.


FF/FF

Ring Pull: The ring pull will be provided as default for both 90⁰ and 180⁰ Bifold Track Shutters. Customer need specify ring pull location on the order form. Ring pull location is measured from the floor to center of the ring pull in height direction. Ring pull color will match the hinge color.

Please refer to below drawing of ring pull position for 180⁰ Bifold Track:











Please refer to below drawing of ring pull position for 90⁰ Bifold Track:









Track Dimension:


Bottom Pivot Bracket for 90 degree bifold:



Extra Magnets will be supplied for Bifold hinges: (only for the most top and bottom hinges)



Side Magnet: applied to the meeting stiles of LR panels





Extra magnet and Side Magnet:



90⁰ Bi Fold Track Shutters Hardware Box

Parts
Wrench
Hinge Pin
Bottom Pivot Bracket
38.1mm screws for bottom pivot bracket
63.5mm screws for Frame



Track Shutters—Bypass

Guidelines and Specs:

		<u>Maximum</u>						
<u>Description</u>	<u>Minimum</u>	1 1⁄4"	17⁄8"	21/2"	3½"; 4½"			
Single-Panel Width (Wood)	6"	20"	30"	36"	42"			
Single-Panel Height	10"	N/A	133"	133"	133"			

Outside Mount

Max frame-to-frame width: window width + 3" Max frame-to-frame height: window height + 4½"

Semi-Inside Mount


Max frame-to-frame width: window width - 1/8" Max frame-to-frame height: window height + 1 3/8"

Inside Mount

Max frame-to-frame width: window width - $^{1}/_{8}$ " Max frame-to-frame height: window height - $^{1}/_{8}$ "



Sussex® NormanTeak™ Shutters 2014 Track Shutters—Bypass



Size Definition

1/16" T Stopper 7/16" Overall Panel Width Frame to Frame Width = Header Width

For IM without side boards

For Semi-Inside/OM without side boards

Overall Panel Width

Frame to Frame Width = Header Width

T Stopper

7/16"


Note: For Semi-Inside/OM without side boards bypass, T Stopper will be supplied.




2014 Track Shutters—Bypass

Top View


Combi - joined Panels (optional)



For shutters with 4 or more panels, please select "side open" or "center open" Side Open




Center Open




Stile: Only 2", 2 1/4" astragal stiles are available, 1 5/8" astragal stile only used for combi-joined panels. Center stile is not available.




Mounting Options (Closed Bypass) Side View




Bottom Guide






Outside Mount






Mounting Options (Closed Bypass with 3 Tracks):



Outside Mount

Inside Mount




Semi-Inside Mount




Mounting Options (Opened Bypass) Only available in 2 ½" and 3 ½" louver sizes

2 1/2" Louver




Outside Mount






3 1/2" Louver








Opened Bypass

Top View



Pitch of track

Louwer	U shape bottor	m guide	Interlocking b	ottom guide
Louver	Regular Tilt Rod Invisible tilt		Regular Tilt Rod	Invisible tilt
2.5"	3 9/16"	2 3/4"	3 9/16"	3 9/16"
3.5"	4 1/2"	3 5/8"	4 1/2"	4 1/2"

Light block thickness for panel

Light bloc	eight blook thiokness for parior						
		U shape bot	ttom guide	Interlocking bottom guide			
Louve	er	Regular Tilt Rod	Invisible tilt	Regular Tilt Rod	Invisible tilt		
2.5"	h1	3/4"	3/4"	3/4"	3/4"		
2.5	h2	1 9/16"	3/4"	1 9/16"	1 9/16"		
3.5"	h1	1 3/16"	1 3/16"	1 3/16"	1 3/16"		
3.5	h2	1 15/16"	1 3/16"	1 15/16"	1 15/16"		



Track Shutters Framing Materials

Framing	Size					
L Shape Header	Header (Closed Bypass)	Header (Opened Bypass)	Supporting Strip			
(2 in 1)	3/4" x 51/2"* (Default for Outside Mount; Optional for Semi-Inside and Inside Mount)	³¼" x 6½" [*] (2½" Louver)	3/4" X 3/4"		1 pc	
Header with Supporting Strip	3/4" x 4½"* (Default for Semi-Inside and Inside Mount; Optional for Outside Mount)	³4" x 7 ¹³ / ₁₆ "* (3½" Louver)				
	Custom [*] ≤ 8"	Custom [*] ≤ 8"				
U Shape Side Frame	Side Frame (Closed Bypass)	Side Frame (Opened Bypass)	Supporting Strip	Side Fascia		
(3 in 1)	3/4" x 5 7/8"* (Default for Outside Mount; Optional for Semi-Inside and Inside Mount)	¾" x 6 ⁵ %" [*] (2½" Louver)		3/83/8" X	2 pcs	
Side Frame with Supporting Strip	3/4" x 4 7/8" (Default for Semi-Inside and Inside Mount; Optional for Outside Mount)	³ ⁄ ₄ " x 81⁄ ₄ " [*] (31⁄ ₂ " Louver)	3⁄4" X 3⁄4"	11/4 "		
& Side Fascia	Custom [*] ≤ 8"	Custom * < 8"				
Top Fascia (Plain/Deco)	in/Deco)					
	½" x 2 ½" (Inside Mount)					
Top Fascia Return						
Retuin	N/A (Inside Mount)					




Hardware Box
Part
Wrench
Nylon Guide
3/4 " screws for Nylon Guide
Support L Bracket (based on the length of header)
2 ½ " screws for support L bracket
3/4 " screws for support L bracket



Special Options

Café Shutters*


- The top of the panel requires a special finish.
 Please indicate "café shutter" when placing orders.
- The shutter does not come with recessed magnet on top.






Double-Hung Shutters*

- For total number of panels, please include panels in both rows.
- For panel configuration, please provide panel fold for one row.
- The default location for the division point is the center unless specified otherwise.
- Horizontal T Post* can be added for increased structural integrity.





Fixed Louvers



^{*} Surcharge applies. Please see Options and Surcharges page for details.



Raised Panel

Available in

- Raised panel with louver combination.
- Raised panel only.

Specifications


- 12" ≤ raised panel section height ≤ 48".
- For 1½" Colonial louver, divider rail is required for panel heights over 50".
- For other louver sizes, divider rail is required for panel heights over 78".
- The maximum panel height is 133".

Raised Panel Location(s)

- Top.
- Middle.
- Bottom.
- All (if panel height does not exceed 48").

Rails

- For a panel with raised panel section only, 3" is the standard size for top, bottom and divider rails.
- The minimum size for top and bottom rails is 3".
- If you are matching raised panels to standard shutter panels, the top rail of the standard shutter panel will match the top rail of the raised panel. Please specify clearly when placing order.




^{*}Surcharge applies. Please see Options and Surcharges page for details.



Hand-Carved Rail *

- Available for top and/or bottom rails.
- Please note that the proportion of the design is based on the height of the rail, not the width of the panel.




^{*}Surcharge applies. Please see Options and Surcharges page for details.



Liberty Arch

- The arch starts and ends 1" from the rail sides.
- The arch height is half of the top rail size (rounded up to ¹/₈" increment).
- The shape of the Arch is based on 3 points taken from the rail.




French Door Contour Collection

- Flush and offset cutout options are available in both curved and square French door
 - ♦ Offset cutout is good option for French Door with molding around the glass.
- All French door cutouts are only available in L frame except Type E and F. The batten is placed behind the Type E/F panel to block light.

Louver size	Batten Width	Batten thickness
1 7/8" & 2 1/2"	<mark>3/4"</mark>	<mark>1"</mark>
<mark>3 1/2"</mark>	<mark>3/4"</mark>	<mark>1 3/8"</mark>
<mark>4 1/2"</mark>	<mark>3/4"</mark>	<mark>1 7/8"</mark>

For measurement details please refer to Form section.



Surcharge applies. Please see Options and Surcharges page for details.



Custom Colors *

Available in Sussex® shutters and Sussex®blinds.

Option (Color Code) Sample Size		Confirmation Process				
Custom Solid (C01)	At least 4" x 4" on a clean, flat surface such as wood or cardboard	All orders require customer's confirmation via actual swatch in the mail before production. Additional shipping and handling fee applies.				
Custom Stain (C02)	At least 4" x 4" on a clean, flat surface such as wood or cardboard	All orders require customer's confirmation via digital photo OR actual swatch in the mail before production. Additional shipping and handling fee applies.				

Note:

- 1) All custom colors will only be finished with the standard gloss used on all Norman products.
- 2) Please note that we will only be able to match the tone instead of the texture or finish of the sample your submit.
- 3) Only one dispute is allowed during the color confirmation process.
- 4) Customer may waive confirmation to shorten production lead time. Norman[®] will not be responsible for any color variation afterwards.

Disclaimer:

Sherwin-William, Sherwin-William Color, Benjamin Moore, Benjamin Moore Classic Colors are registered trademarks or trademarks of their respective owners. All other trademarks mentioned herein are the property of Norman International, Inc. and/or its affiliates in the U.S. and certain other countries. Reference herein to the commercial products or service of others by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement.

^{*}Surcharge applies. Please see Options and Surcharges page for details.




Specialties

Specialty Shutters

Specialty shutters are made of premium solid wood, finished to match the beauty of all Norman shutters. Templates are required if it is an imperfect specialty. Delivery time is 8 weeks from the order confirmation date for all specialty shutters. Please refer to Specialties and Template Requirement sections for details.

All frames for specialty shutters will be made as solid frames (not with an insert). However, if there is a regular shutter below a specialty shutter and the frames for both shutters are separated by a divider strip, then the top frame will be made as a solid frame but the bottom frames will be made as regular frames with inserts. If the top frames and the side frames are not separated by a divider strip, both side frames and the bottom frames will be made as solid frames.



^{*}Surcharge applies. Please see Options and Surcharges page for details.



Pricing

1) By Max Frame-to-Frame N	leasurement:						
Regular Shutter							
Inside and Outside Mount	Width	Х	Height	/ 144	Х	\$/sq ft	
Track Shutter**							
Inside		Width	Х	Height	/ 144	Х	\$/sq ft
Semi-Inside and Outside Mour	nt	Width	х	(Height-1½")	/ 144	Х	\$/sq ft
2) By Net Panel Measuremer	nt:	Width	х	Height	/ 144	х	\$/sq ft
3) By Window Size:							
	4-sided	(Width+4")	х	(Height+4")	/ 144	х	\$/sq ft
	3-sided with Deco Sill Frame	(Width+4")	х	(Height+5")	/ 144	х	\$/sq ft
	3-sided with Designer Sill Cap	(Width+4")	х	(Height+8")	/ 144	х	\$/sq ft
2" Camber Deco Frame	3-sided with Sill Plate	(Width+4")	х	(Height+4")	/ 144	х	\$/sq ft
2" Classic Deco Frame	3-sided	(Width+4")	х	(Height+2")	/ 144	х	\$/sq ft
	2-sided with Deco Sill Frame	(Width+4")	х	(Height+3")	/ 144	х	\$/sq ft
	2-sided with Designer Sill Cap	(Width+4")	х	(Height+6")	/ 144	х	\$/sq ft
	2 sided with Sill Plate	(Width+4")	х	(Height+2")	/ 144	х	\$/sq ft
	2-sided	(Width+4")	х	(Height)	/ 144	х	\$/sq ft
	4-sided	(Width+6")	х	(Height+6")	/ 144	х	\$/sq ft
	3-sided with Deco Sill Frame	(Width+6")	х	(Height+6")	/ 144	х	\$/sq ft
	3-sided with Designer Sill Cap	(Width+6")	х	(Height+9")	/ 144	х	\$/sq ft
	3-sided with Sill Plate	(Width+6")	х	(Height+6")	/ 144	х	\$/sq ft
3" Ridge Deco Frame	3-sided	(Width+6")	х	(Height+3")	/ 144	х	\$/sq ft
	2-sided with Deco Sill Frame	(Width+6")	х	(Height+3")	/ 144	х	\$/sq ft
	2-sided with Designer Sill Cap	(Width+6")	х	(Height+6")	/ 144	х	\$/sq ft
	2-sided with Sill Plate	(Width+6")	х	(Height+3")	/ 144	х	\$/sq ft
	2-sided	(Width+6")	х	(Height)	/ 144	х	\$/sq ft
	4-sided	(Width+4 1/2")	х	(Height+41/2")	/ 144	х	\$/sq ft
	3-sided with Deco Sill Frame	(Width+4 ½")	х	(Height+51/4")	/ 144	х	\$/sq ft
	3-sided with Designer Sill Cap	(Width+4 ½")	х	(Height+81/4")	/ 144	х	\$/sq ft
	3-sided with Sill Plate	(Width+4 ½")	х	(Height+41/2")	/ 144	х	\$/sq ft
3" Crown Z Frame	3-sided	(Width+4 ½")	х	(Height+21/4")	/ 144	х	\$/sq ft
	2-sided with Deco Sill Frame	(Width+4 ½")	х	(Height+3")	/ 144	х	\$/sq ft
	2-sided with Designer Sill Cap	(Width+4 ½")	х	(Height+6")	/ 144	х	\$/sq ft
	2-sided with Sill Plate	(Width+4 ½")	х	(Height+21/4")	/ 144	х	\$/sq ft
	2-sided	(Width+4 ½")	х	(Height)	/ 144	х	\$/sq ft

^{*}This table is for pricing use only.

**Surcharge for tracks and boxout are not included.



Pricing

	4-sided	(Width+2 1/2")	х	(Height+2½")	/ 144	х	\$/sq ft
	3-sided with Deco Sill Frame	(Width+2 1/2")	х	(Height+41/4")	/ 144	х	\$/sq ft
	3-sided with Designer Sill Cap	(Width+2 1/2")	х	(Height+71/4")	/ 144	х	\$/sq ft
	3-sided with Sill Plate	(Width+2 1/2")	Х	(Height+2½")	/ 144	Х	\$/sq ft
2" Bel Air Z Frame	3-sided	(Width+2 1/2")	х	(Height+11/4")	/ 144	х	\$/sq ft
	2-sided with Deco Sill Frame	(Width+2 1/2")	х	(Height+3")	/ 144	х	\$/sq ft
	2-sided with Designer Sill Cap	(Width+2 1/2")	х	(Height+6")	/ 144	х	\$/sq ft
	2-sided with Sill Plate	(Width+2 1/2")	х	(Height+11/4")	/ 144	х	\$/sq ft
	2-sided	(Width+2 1/2")	х	(Height)	/ 144	х	\$/sq ft
	4-sided	(Width+2")	х	(Height+2")	/ 144	х	\$/sq ft
	3-sided with Deco Sill Frame	(Width+2")	х	(Height+4")	/ 144	х	\$/sq ft
	3-sided with Designer Sill Cap	(Width+2")	х	(Height+7")	/ 144	х	\$/sq ft
1 ½ " Bullnose Z Frame/	3-sided with Sill Plate (N/A w/ Tilt out Z)	(Width+2")	х	(Height+2")	/ 144	х	\$/sq ft
1 ¼ " Beaded Z Frame/	3-sided	(Width+2")	х	(Height+1")	/ 144	х	\$/sq ft
Bullnose Tilt Out Z Frame	2-sided with Deco Sill Frame	(Width+2")	Х	(Height+3")	/ 144	х	\$/sq ft
	2-sided with Designer Sill Cap	(Width+2")	Х	(Height+6")	/ 144	х	\$/sq ft
	2-sided with Sill Plate (N/A w/ Tilt out Z)	(Width+2")	х	(Height+1")	/ 144	х	\$/sq ft
	2-sided	(Width+2")	Х	(Height)	/ 144	х	\$/sq ft
	Inside	Width	х	Height	/ 144	х	\$/sq ft
	Outside 4-sided	(Width+3")	х	(Height+3")	/ 144	х	\$/sq ft
	Outside 3-sided with Deco Sill Frame	(Width+3")	х	(Height+41/2")	/ 144	х	\$/sq ft
Vintage Hang Strip	Outside 3-sided with Designer Sill Cap	(Width+3")	х	(Height+7½")	/ 144	х	\$/sq ft
viilage riang strip	Outside 3-sided	(Width+3")	х	(Height+1½")	/ 144	х	\$/sq ft
	Outside 2-sided with Deco Sill Frame	(Width+3")	х	(Height+3")	/ 144	х	\$/sq ft
	Outside 2-sided with Designer Sill Cap	(Width+3")	х	(Height+6")	/ 144	х	\$/sq ft
	Outside 2-sided	(Width+3")	х	(Height)	/ 144	х	\$/sq ft
	Inside (max frame to frame measurement only)	Width	х	Height	/ 144	х	\$/sq ft
	Outside 4-sided	(Width+3")	х	(Height+3")	/ 144	х	\$/sq ft
Vintage L Frame/	Outside 3-sided with Deco Sill Frame	(Width+3")	х	(Height+4½")	/ 144	х	\$/sq ft
Beaded L Frame/	Outside 3-sided with Designer Sill Cap	(Width+3")	х	(Height+7½")	/ 144	х	\$/sq ft
Colonial L Frame/	Outside 3-sided	(Width+3")	х	(Height+1½")	/ 144	х	\$/sq ft
Bullnose L Frame/	Outside 2-sided with Deco Sill Frame	(Width+3")	х	(Height+3")	/ 144	х	\$/sq ft
Rope L Frame	Outside 2-sided with Designer Sill Cap	(Width+3")	х	(Height+6")	/ 144	х	\$/sq ft
	Outside 2-sided	(Width+3")	х	(Height)	/ 144	х	\$/sq ft
Track Shutter**	•		,	L			<u>. </u>
Inside and Semi-Inside Mount		Width	_x	Height	/144	x	\$/sq ft
Outside Mount		(Width+3")	х	(Height+3")	/144		\$/sq ft
	. ,		· - ,			•	

^{*}This table is for pricing use only.

**Surcharge for tracks and boxout are not included.



Options & Surcharges

Option	Surcharge	Remark
1¼" Louver	10%	
1%" Louver	10%	
Beaded L Frame with 1/4" Thick Light Block	No surcharge	
L Frame with ½" & 1" Buildout	5%	
Notch Out L Frame	10%	
Deco Frame with ½", 1" & 1½" Extension	5%	
Outline Filtersian	400/	Up to 2" for L Frames, Deco Frames and Hang Strip (OM)
Custom Extension	10%	Up to 1" for Z Frames (not available for Tilt Out Z frame)
T Post	No surcharge	
T Post Extension	5%	Up to 2"
Custom width T Post	5%	Up to 7½"
90 degree Corner Post & 135 degree Bay Post	No surcharge	
Double Hung / Horizontal 1¾" T Post	10%	
Custom Angle/Depth Bay Post	5%	Up to 2" for custom depth
Extra Light Block	Charge per linear ft	Please contact your Customer Account Specialist for details
Scribe Trim	Charge per linear ft	Please contact your Customer Account Specialist for details
Center Tilt Rod	No surcharge	
Offset Tilt Rod	5%	
InvisibleTilt™	10%	Not available in 11/4" or 11/6" louvers.
Optimal™ Antimicrobial Treatment	10%	
Café Shutters	30%	Surcharge applies when the frame exceeds 5" beyond the top of the panel.
Hand Carved Rail	See specialty surcharge	
Raised Panel	See specialty surcharge	Please contact your Customer Account Specialist for details
Fixed Louver Panel	No surcharge	Please indicate fixed position: up/down and open/close
French Door Cutout	See specialty surcharge	Please contact your Customer Account Specialist for details
Track (Bi Fold / Bypass)	40%	
Liberty Arch	See specialty surcharge	
Specialties	See specialty surcharge	Please contact your Customer Account Specialist for details
Stainless Steel Hinges	3%	
Custom Color	See specialty surcharge	Please contact your Custom Account Specialist for details
PerfectTilt (regular)	Per motor, per remote control	Please contact your Custom Account Specialist for details
PerfectTilt (solar)	Per motor, per remote control	Please contact your Custom Account Specialist for details



Appendix

Color Coordination Chart (Solid)

Code	Sussex Solid	Hinge
001	Pure White	White
003	Silk White	White
004	Bright White	White
006	Pearl	Pearl
007	Ivory Lace	Pearl
800	Marshmallow	Pearl
009	Creamy	Bisque
011	Cameo	Bisque
012	Crisp Linen	Bisque
013	Bisque	Bisque
016	Butter	Bisque
019	String	Bisque
030	Moondust	Nickel Plated
032	Sea Mist	Nickel Plated
046	lce	White
048	Chai	Nickel Plated
049	Stone Grey	Nickel Plated
051	Brown Grey	Nickel Plated
053	Clay	Nickel Plated
063	Decorators White	White
836	Classic Black	Black



Color Coordination Chart (Stain)


Code	Sussex Stain	Hinge Color
108	Rustic Gray	Antique Brass
110	Limed White	White
114	Taupe	Nickel Plated
200	Natural	Antique Brass
202	Golden Oak	Antique Brass
204	Oak Mantel	Antique Brass
205	Goldenrod	Antique Brass
206	Pecan	Antique Brass
211	Cherry	Antique Brass
212	Dark Teak	Antique Brass
214	Cocoa	Antique Brass
215	Cordovan	Antique Brass
219	Mahogany	Antique Brass
220	New Ebony	Antique Brass
221	Black Walnut	Antique Brass
227	Red Oak	Antique Brass
229	Rich Walnut	Antique Brass
230	Old Teak	Antique Brass
231	Spring Rose	Antique Brass
232	Red Mahogany	Antique Brass
233	Dark Mahogany	Antique Brass
237	Wenge	Antique Brass
242	Auburn	Antique Brass
247	Bark	Antique Brass
248	Pretzel	Antique Brass
249	Acorn	Antique Brass
250	Sumatra	Antique Brass
251	Raisin	Antique Brass
252	Toffee	Antique Brass




Louver Depth Clearance

Standard Tilt Rod


Offset Tilt Rod








Louver Depth Clearance for Specific Frames




1 1/4" Beaded Z Frame

1 1/2" Bullnose Z Frame




NT n-4





Beaded L Frame W/1/4" Light Block


Beaded L Frame



Beaded L W/1/2" Buildout


Beaded L W/1" Buildout





Vintage L Frame W/1/4" Light Block


Vintage L Frame



Vintage L W/1/2" Buildout

Vintage L W/1" Buildout

Sussex® NormanTeak™ Shutters



Hang Strip (Behind the panel)

